

0648

Downlight for recessed installation



Description

Downlight for recessed installation with body made in zinc coated steel. IP20. All internal wiring is heat resistant. Trims in white, chrome or brass. Decors available. The downlight is available with or without transformer.

For accommodation areas, public areas etc. This decorative halogen spot for low voltage halogen lamps with cool beam reflectors is designed to meet the great demands of our customers.


Technical description

Light source	QR (GU 5,3)	Dimension	Ø = 11
Housing	Zinc coated steel	(mm)	H = 163

0648

Downlight for recessed installation

Measurement drawings



0648 GU 5,3 Standard

Item description	Item no.	Minimum Voltage -10% (V)	Connection Type
0648/MAX50/230/12/IP20/PLUG WAGO+CABLE/SILVER /MOUNTING HIGHT	0648373461	230	3-pole Wago plug
0648/MAX50/230/12/IP20/PLUG WAGO+CABLE/SILVER /MOUNTING HIGHT	0648373470	230	3-pole Wago plug
0648/MAX50/230/12/IP20/PLUG WAGO+CABLE/WHITE /MOUNTING HIGHT	0648573460	230	Wag plug
0648/MAX50/230/12/IP20/PLUG ENSTO/SILVER/GU5,3	0648374101	230	3-pole plug ENSTO NAC 31S.W
0648/MAX50/230/12/IP20/GX5,3/PLUG ENSTO/SILVER	0648374404	230	3-pole plug ENSTO NAC 31S.W